

MINO 60 S CIRCLE

1500 direct / indirect

suspended
034-721163GH



Project / Type _____

Notes _____

Count / Date _____



General	
Ceiling , Suspended	_____
grey , RAL9006 ¹	_____
IP20	_____
indirect 5800 lm	_____
direct 10300 lm	_____
total 16100 lm	_____

LED	
4000 K	_____
CRI ≥ 80	_____
L90 / 50000 h	_____
photobio. safety RG 0 - no Risk	_____
initial MacAdam ≤ 3 SDCM	_____
MR 0.72	_____
MDER 0.65	_____

Optical	
High Performance Opal	_____
opal (lambertsch)	_____
PstLM ≤ 1.0 ²	_____
SVM ≤ 0.4 ²	_____


Ring-shaped light fitting in rolled and seamlessly welded extruded aluminium profile; flat design; suspended luminaire with 1500mm cable suspension; height adjustment without tools; incl. feed (white); surface grey powder coated; extruded profile for improved thermal management; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; HPO (High Performance Opal) cover for uniform illumination; direct/indirect light emission for additional accentuation of the ceiling; indirect light component with integrated PC boards and high quality lens system for maximum, homogeneous ceiling illumination; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; incl. DALI-2 converter; converter included in canopy; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Electrical	
DALI-2	_____
system 119 W	_____
PC1 220-240V	_____
system 135 lm/W ³	_____
5 DALI Addr.	_____


Physical	
cable 1500 mm	_____
diameter 1560 mm	_____
height 60 mm	_____
centerline radius 750 mm	_____
13 kg	_____

¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. optical losses and the efficiency of the operating device (converter)

Light distribution



Product drawing



Installation instructions

Lighting calculator

