

# TWIST 100

trim

048-1121118S 048-2796318 002-90789



Project / Type
Notes
Count / Date



## General

Ceiling , Recessed
tilt max 45°
rotation 360°
black , RAL9005 <sup>1</sup>
Mounting set jet black
front IP20 , back IP20
3140 lm

## LED

4000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM

## Optical

spot
beam angle 20°
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>

## Electrical

DALI-2
25.3 W
inset 22.7 W
650 mA
PC2 220-240V
124 lm/W
1 DALI Addr.

## Physical


diameter 118 mm
height 99 mm
0.26 kg

## Cutout

diameter 108 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 160 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)



## Light distribution



spot 20°

h (m)	E0° (lx)	ø (m)
1	17500	0.34
2	4400	0.69
3	1900	1.03
4	1100	1.38
5	700	1.72

## Product drawing



## Installation instructions



## Lighting calculator

