

# TWIST 100

trimless

048-1121017M 048-2796117 002-90780



Project / Type

Notes

Count / Date



## General

Ceiling , Recessed

tilt max 45°

rotation 360°

white , RAL9016 <sup>1</sup>

Mounting set RAL Traffic white

front IP20 , back IP20

3150 lm

## LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 98 , R<sub>r</sub>: 91 , R<sub>(1-15)</sub>: 93

MR 0.54

MDER 0.49

## Optical

medium

beam angle 27°

P<sub>stLM</sub> ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

## Electrical

non DIM

system 25.3 W

inset 22.7 W

650 mA

PC2 220-240V

system 125 lm/W<sup>3</sup>

inset 139 lm/W<sup>4</sup>

## Physical

diameter 105 mm

height 99 mm

0.49 kg

## Cutout

diameter 106 mm


min. ceiling thickness 12.5 mm

max. ceiling thickness 25 mm

recessed depth 160 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> incl. optical losses and the efficiency of the operating device (converter)  
<sup>4</sup> incl. optical losses

## Light distribution



medium 27°

h (m)	E0° (lx)	ø (m)
1	10100	0.49
2	2500	0.97
3	1100	1.46
4	600	1.95
5	400	2.43

## Product drawing



## Installation instructions



## Lighting calculator

