

INDIRECT low power

MOVE IT PRO
086-6880630B



Project / Type


Notes

Count / Date



Linear light inset made of plastic; light inset, incl. high power adapter + converter can be installed flexibly and without tools; flush with profile system; power supplied via MOVE IT PRO system track profile; with indirect light component for additional accentuation of the ceiling; high quality lens system for maximum, homogeneous ceiling illumination; passive cooling of the LEDs through improved heat sink geometry; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC2; 220-240 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Ceiling , Track

indirect batwing low power

white

1750 lm/m

IP20

7650 lm

LED

4000 K

CRI ≥ 80

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.72

MDER 0.65

Optical

batwing

UGR < 10 , $\geq 65^\circ$ <1500 cd/m²

Electrical

DALI-2

220-240 V

system 47 W

PC2

system 163 lm/W¹

1 DALI Addr.

11 W/m

Physical

length 4412 mm

width 24 mm

height 6 mm

¹ incl. optical losses and the efficiency of the operating device (converter)

Installation instructions



Lighting calculator

