

# LOUVER WIDE

MOVE IT PRO  
086-6430034X



Project / Type \_\_\_\_\_


Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



Linear light inset made of plastic; light inset, incl. high power adapter + converter can be installed flexibly and without tools; flush with profile system; power supplied via MOVE IT PRO system track profile; high quality reflector with micro-faceted, aluminum-vaporised surface; chrome reflector; precise radiation characteristic with symmetrical light distribution; for use in schools and offices;  $UGR \leq 19$ ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above  $65^\circ \leq 1500 \text{ cd/m}^2$ ; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam  $\leq 3 \text{ SDCM}$ ;  $CRI \geq 90$ ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC2 220-240V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



## General

Ceiling , Track \_\_\_\_\_

reflector wide \_\_\_\_\_

chrome reflector \_\_\_\_\_

2230 lm/m \_\_\_\_\_

IP20 \_\_\_\_\_

4450 lm \_\_\_\_\_

## LED

3000 K \_\_\_\_\_

$CRI \geq 90$  \_\_\_\_\_

L90 / 50000 h \_\_\_\_\_

initial MacAdam  $\leq 3 \text{ SDCM}$  \_\_\_\_\_

$R_g: 99, R_f: 91, R_{(1-15)}: 89$  \_\_\_\_\_

MR 0.61 \_\_\_\_\_

MDER 0.55 \_\_\_\_\_

## Optical

super wide flood \_\_\_\_\_

$UGR < 19, \geq 65^\circ < 1500 \text{ cd/m}^2$  \_\_\_\_\_

$PstLM \leq 1.0^1$  \_\_\_\_\_

$SVM \leq 0.4^1$  \_\_\_\_\_

## Electrical

DALI-2 \_\_\_\_\_

34 W \_\_\_\_\_

PC2 220-240V \_\_\_\_\_

131 lm/W \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_

17 W/m \_\_\_\_\_

## Physical

length 2000 mm \_\_\_\_\_

width 43 mm \_\_\_\_\_

height 13 mm \_\_\_\_\_

<sup>1</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Lighting calculator

