

MOVE IN 45 square

trim

063-8421518S 063-8842117 002-90720



Project / Type _____

Notes _____

Count / Date _____



220-240V X-PERT CRI ≥ 90 DALI 1ADDR X-PERT

General

Ceiling , Semi-Recessed
black , RAL9005 ¹
Mounting set traffic white
IP20
1100 lm

LED

3000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R_g: 100 , R_f: 91 , R₍₁₋₁₅₎: 88
MR 0.59
MDER 0.53

Optical

spot
beam angle 12°
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Electrical

DALI-2
15.0 W
inset 12.8 W
37 Vf
350 mA
PC2 220-240V
73 lm/W
1 DALI Addr.

Physical


trim
diameter 78 mm
height 105 mm
0.24 kg

Cutout

diameter 70 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 175 mm

¹ RAL code ² Value of containing product at full load (undimmed)



Light distribution



spot 12°

h (m)	E0° (lx)	ø (m)
1	13900	0.21
2	3500	0.42
3	1500	0.63
4	900	0.84
5	600	1.06

Product drawing



Installation instructions



Lighting calculator

