

MOVE IN 45 square

trimless

063-8421516V 063-8832117 002-90729



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Semi-Recessed _____

brushed aluminium _____

Mounting set traffic white _____

IP20 _____

346 lm _____

LED

3000 K _____

CRI \geq 90 _____

L85 / 50000 h _____

initial MacAdam \leq 3 SDCM _____

R_g: 98 , R_r: 91 , R_{t(1-15)}: 89 _____

MR 0.6 _____

MDER 0.55 _____

Optical

super spot _____

beam angle 8° _____

PstLM \leq 1.0 ¹ _____

SVM \leq 0.4 ¹ _____

Electrical

DALI-2 _____

9.2 W _____

inset 6.9 W _____

11 Vf _____

600 mA _____

PC2 220-240V _____

38 lm/W _____

1 DALI Addr. _____

Physical

trimless _____

diameter 80 mm _____

height 105 mm _____

0.21 kg _____

Cutout

diameter 65 mm _____

min. ceiling thickness 9 mm _____

max. ceiling thickness 25 mm _____

recessed depth 175 mm _____

¹ Value of containing product at full load (undimmed)


Light distribution



super spot 8°

h (m)	E0° (lx)	ø (m)
1	12100	0.14
2	3000	0.28
3	1300	0.41
4	800	0.55
5	500	0.69

Product drawing



Installation instructions



Lighting calculator

