

# MOVE IN 45 square

trim

063-8421516S 063-8842117 002-90720



Project / Type

Notes

Count / Date



## General

Ceiling , Semi-Recessed

brushed aluminium

Mounting set traffic white

IP20

1090 lm

fixture 86 lm/W<sup>1</sup>

## LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 91 , R<sub>f(1-5)</sub>: 88

MR 0.59

MDER 0.53

## Optical

spot

beam angle 12°

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

## Electrical

DALI-2

220-240 V

system 15.0 W

fixture 12.7 W

37 Vf

350 mA

PC2

1 DALI Addr.

## Physical

trim

diameter 78 mm

height 105 mm

0.24 kg

## Cutout

diameter 70 mm


min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 175 mm

<sup>1</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.  
<sup>2</sup> Value of containing product at full load (undimmed)

## Light distribution



spot 12°

h (m)	E0° (lx)	ø (m)
1	13800	0.21
2	3400	0.42
3	1500	0.63
4	900	0.84
5	600	1.06

## Product drawing



## Installation instructions



## Lighting calculator

