

# MOVE IN 45 square

trimless


063-8421418S 063-8832117 002-90720



Project / Type

Notes

Count / Date



## General

Ceiling , Semi-Recessed  
black , RAL9005 <sup>1</sup>  
Mounting set traffic white  
IP20  
1020 lm

## LED

2700 K  
CRI ≥ 90  
L80 / 50000 h  
initial MacAdam ≤ 2 SDCM  
R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>(1-15)</sub>: 89  
MR 0.53  
MDER 0.48

## Optical

spot  
beam angle 12°  
PstLM ≤ 1.0 <sup>2</sup>  
SVM ≤ 0.4 <sup>2</sup>

## Electrical

DALI-2  
14.5 W  
inset 12.3 W  
37 Vf  
350 mA  
PC2 220-240V  
70 lm/W  
1 DALI Addr.

## Physical


trimless  
diameter 80 mm  
height 105 mm  
0.21 kg

## Cutout

diameter 65 mm  
min. ceiling thickness 9 mm  
max. ceiling thickness 25 mm  
recessed depth 175 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)


## Light distribution



spot 12°

h (m)	E0 <sup>3</sup> (lx)	ø (m)
1	12900	0.21
2	3200	0.42
3	1400	0.63
4	800	0.84
5	500	1.06

## Product drawing



## Installation instructions



## Lighting calculator



[063-8421418S 063-8832117 002-90720] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.

© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

03.07.2024

1 / 1