

# MOVE IN 45 square

trimless

063-8421417S 063-8832117 002-90720



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



220-240V X-PERT CRI ≥ 90 DALI 1ADDR X-PERT

## General

Ceiling , Semi-Recessed  
white , RAL9016 <sup>1</sup>  
IP20  
1040 lm

## LED

2700 K  
CRI ≥ 90  
L80 / 50000 h  
initial MacAdam ≤ 2 SDCM  
R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89  
MR 0.53  
MDER 0.48

## Optical

spot  
beam angle 12°  
PstLM ≤ 1.0 <sup>2</sup>  
SVM ≤ 0.4 <sup>2</sup>


## Electrical

DALI-2  
15.0 W  
inset 12.7 W  
37 Vf  
350 mA  
PC2 220-240V  
69 lm/W  
1 DALI Addr.

## Physical

trimless  
diameter 80 mm  
height 105 mm  
0.21 kg


## Light distribution



spot 12°

h (m)	E0° (lx)	ø (m)
1	13200	0.21
2	3300	0.42
3	1500	0.63
4	800	0.84
5	500	1.06

## Product drawing



## Cutout

diameter 65 mm  
min. ceiling thickness 9 mm  
max. ceiling thickness 25 mm  
recessed depth 175 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Lighting calculator

