

MOVE IN 45 flex round

trimless

063-8221416V 063-8812117 002-90729



Project / Type

Notes

Count / Date




General
Ceiling , Semi-Recessed
tilt max 90°
rotation 360°
brushed aluminium
Mounting set traffic white
IP20
400 lm

LED
2700 K
CRI ≥ 90
L85 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 99 , R _r : 91 , R _{t(1-15)} : 89
MR 0.54
MDER 0.49

Optical
super spot
beam angle 8°
PstLM ≤ 1.0 ¹
SVM ≤ 0.4 ¹


Electrical
DALI-2
9.2 W
inset 6.9 W
11 Vf
600 mA
PC2 220-240V
43 lm/W
1 DALI Addr.

Light distribution



super spot 8°		
h (m)	E0° (lx)	ø (m)
1	14000	0.14
2	3500	0.28
3	1600	0.41
4	900	0.55
5	600	0.69

Product drawing



Physical
trimless
diameter 75 mm
height 106 mm
0.45 kg

Cutout
diameter 65 mm
min. ceiling thickness 9 mm
max. ceiling thickness 25 mm
recessed depth 195 mm

¹ Value of containing product at full load (undimmed)

Installation instructions

Lighting calculator

