

# MOVE IN 45 flex round

trim

063-8221518S 063-8822118 002-90720



Project / Type

Notes

Count / Date



## General

Ceiling , Semi-Recessed

tilt max 90°

rotation 360°

black , RAL9005 <sup>1</sup>

Mounting set jet black

IP20

1100 lm

## LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 91 , R<sub>f(1-5)</sub>: 88

MR 0.59

MDER 0.53

## Optical

spot

beam angle 12°

P<sub>stLM</sub> ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

## Electrical

DALI-2

system 15.0 W

inset 12.8 W

37 Vf

350 mA

PC2 220-240V

system 73 lm/W<sup>3</sup>

inset 86 lm/W<sup>4</sup>

1 DALI Addr.

## Physical

trim

diameter 77 mm

height 107 mm

0.49 kg

## Cutout

diameter 65 mm

min. ceiling thickness 2 mm


max. ceiling thickness 25 mm

recessed depth 195 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> incl. optical losses and the efficiency of the operating device (converter)  
<sup>4</sup> incl. optical losses

Round spotlight element in aluminium; surface black powder coated; installation without tools in mounting set due to patented ball catch system; recessed light with trim jet black; suitable for ceiling thickness of 2-25 mm; spotlight element height adjustable without tools: flush with the ceiling, or extended 25 mm or 35 mm; 360° rotatable and 90° tiltable; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality, aluminium, vapour deposition coated reflector with faceted lens design; precise radiation characteristic with 12° beam; good glare control through recessed light point level; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC2 220-240V; incl. DALI-2 converter; converter wired secondary side; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



spot 12°

h (m)	E0° (lx)	ø (m)
1	13900	0.21
2	3500	0.42
3	1500	0.63
4	900	0.84
5	600	1.06

## Product drawing



# MOVE IN 45 flex round

trim

063-8221518S 063-8822118 002-90720



Project / Type

Notes

Count / Date

Installation  
instructions



Lighting  
calculator

