

# MOVE IN 45 flex round

trimless

063-8221516F 063-8812117 002-90728



Project / Type

Notes

Count / Date




<b>General</b>
Ceiling , Semi-Recessed
tilt max 90°
rotation 360°
brushed aluminium
IP20
1310 lm

<b>LED</b>
3000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R <sub>g</sub> : 100 , R <sub>f</sub> : 91 , R <sub>f1-15</sub> : 88
MR 0.59
MDER 0.53

<b>Optical</b>
flood
beam angle 36°
PstLM ≤ 1.0 <sup>1</sup>
SVM ≤ 0.4 <sup>1</sup>

<b>Electrical</b>
DALI-2
system 15.9 W
inset 13.5 W
36 Vf
400 mA
PC2 220-240V
system 82 lm/W <sup>2</sup>
inset 97 lm/W <sup>3</sup>
1 DALI Addr.

## Light distribution



flood 36°

h (m)	E0° (lx)	ø (m)
1	3900	0.65
2	980	1.29
3	430	1.94
4	240	2.59
5	160	3.23

## Product drawing



<b>Physical</b>
trimless
diameter 75 mm
height 106 mm
0.36 kg

<b>Cutout</b>
diameter 65 mm
min. ceiling thickness 9 mm
max. ceiling thickness 25 mm
recessed depth 195 mm

<sup>1</sup> Value of containing product at full load (undimmed)  
<sup>2</sup> incl. optical losses and the efficiency of the operating device (converter)  
<sup>3</sup> incl. optical losses

## Installation instructions

## Lighting calculator

