

MOVE IN 45 flex round

trim

063-8221514S 063-8822118 002-90720



Project / Type

Notes

Count / Date



General
Ceiling , Semi-Recessed
tilt max 90°
rotation 360°
chrome
Mounting set jet black
IP20
1100 lm
fixture 86 lm/W ¹

LED
3000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R _g : 100 , R _f : 91 , R _{1-15} : 88
MR 0.59
MDER 0.53

Optical
spot
beam angle 12°
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Electrical
DALI-2
220-240 V
system 15.0 W
fixture 12.8 W
37 Vf
350 mA
PC2
1 DALI Addr.


Physical
trim
diameter 77 mm
height 107 mm
0.49 kg

Cutout
diameter 65 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 195 mm

¹ incl. consideration of optical losses & internal control unit losses


² Value of containing product at full load (undimmed)

Light distribution



spot 12°		
h (m)	E0° (lx)	ø (m)
1	13900	0.21
2	3500	0.42
3	1500	0.63
4	900	0.84
5	600	1.06

Product drawing



Installation instructions



Lighting calculator

