

# MOVE IN 45 round

trim

063-8121516M 063-8822118 002-90728



|                |
|----------------|
| Project / Type |
| Notes          |
| Count / Date   |



## General

|                              |
|------------------------------|
| Ceiling , Semi-Recessed      |
| brushed aluminium            |
| Mounting set jet black       |
| IP20                         |
| 1270 lm                      |
| fixture 95 lm/W <sup>1</sup> |

## LED

|   |
|---|
| 3000 K  |
| CRI ≥ 90  |
| L80 / 50000 h   |
| initial MacAdam ≤ 2 SDCM  |
| R <sub>g</sub> : 100 , R <sub>f</sub> : 91 , R <sub>f(1-5)</sub> : 88 |
| MR 0.59   |
| MDER 0.53   |

## Optical

|                          |
|--------------------------|
| medium                   |
| beam angle 24°           |
| PstLM ≤ 1.0 <sup>2</sup> |
| SVM ≤ 0.4 <sup>2</sup>   |

Round spotlight element in aluminium; surface brushed aluminium; installation without tools in mounting set due to patented ball catch system; recessed light with trim jet black; suitable for ceiling thickness of 2-25 mm; spotlight element height adjustable without tools: flush with the ceiling, or extended 25 mm or 35 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality, aluminium, vapour deposition coated reflector with faceted lens design; precise radiation characteristic with 24° beam; good glare control through recessed light point level; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC2; 220-240 V; incl. DALI-2 converter; converter wired secondary side; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Electrical

|                |
|----------------|
| DALI-2         |
| 220-240 V      |
| system 15.9 W  |
| fixture 13.5 W |
| 36 Vf          |
| 400 mA         |
| PC2            |
| 1 DALI Addr.   |

## Light distribution



medium 24°

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1     | 6120     | 0.43  |
| 2     | 1530     | 0.86  |
| 3     | 680      | 1.30  |
| 4     | 380      | 1.73  |
| 5     | 240      | 2.16  |

## Product drawing



## Physical

|                |
|----------------|
| trim           |
| diameter 77 mm |
| height 107 mm  |
| 0.38 kg        |

## Cutout

|                              |
|------------------------------|
| diameter 65 mm               |
| min. ceiling thickness 2 mm  |
| max. ceiling thickness 25 mm |
| recessed depth 195 mm        |

<sup>1</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.  
<sup>2</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Lighting calculator



# MOVE IN 45 round

trim

063-8121516M 063-8822118 002-90728



Project / Type

Notes

Count / Date

## Maintenance Factors

| Operating Time [h] | 10 000                       | 20 000 | 30 000  | 40 000 | 50 000 |
|--------------------|------------------------------|--------|---|--------|--------|
| LLMF               | 0.96                         | 0.92   | 0.89  | 0.85   | 0.82   |
| LSF                | 1                            | 1      | 1   | 1      | 1      |
| MF                 | LMF × RSMF × LLMF × LSF      |        | RSMF <sup>a</sup> Room Surface Maintenance Factor |        |        |
| MF                 | Maintenance Factor           |        | LLMF Lamp Lumens Maintenance Factor               |        |        |
| LMF <sup>a</sup>   | Luminaire Maintenance Factor |        | LSF Lamp Survival Faktor                          |        |        |

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Circuit Breaker Types

| Automatic Circuit Breaker Type | Number of Fixtures |
|--------------------------------|--------------------|
| B10                            | 36                 |
| B13                            | 47                 |
| B16                            | 58                 |
| C10                            | 36                 |
| C13                            | 78                 |
| C16                            | 58                 |

## Components

### MOUNTING HOUSING with trim

|           |        |                   |
|-----------|--------|-------------------|
| COLOUR    | Ø (MM) | ARTICLE NUMBER(S) |
| jet black | 77     | 063-8822118       |



### POWER SUPPLY

|            |                   |
|------------|-------------------|
| L-W-H (MM) | ARTICLE NUMBER(S) |
| 197-29-21  | 002-90728         |



## Mounting accessories

### SPECIAL MOUNTING TOOL

|  |        |                   |
|--|--------|-------------------|
| TYPE   | Ø (MM) | ARTICLE NUMBER(S) |
| necessary to install mounting housing trimless | 100    | 063-8912110       |



## Optional electrical accessories

### DIN RAIL POWER SUPPLY

|       |            |                   |
|-------|------------|-------------------|
| TYPE  | L-W-H (MM) | ARTICLE NUMBER(S) |
| 160 W | 72-90-63   | 005-6520210       |



### DIN RAIL LED DRIVER

|                                |            |                   |
|--------------------------------|------------|-------------------|
| TYPE                           | L-W-H (MM) | ARTICLE NUMBER(S) |
| DALI-2   200-1050 mA   2 x 42W | 36-88-59   | 005-6121030       |



## Optical accessories

### HONEYCOMB LOUVER

|           |        |                   |
|-----------|--------|-------------------|
| COLOUR    | Ø (MM) | ARTICLE NUMBER(S) |
| jet black | 42     | 007-1965188       |



# MOVE IN 45 round

trim

063-8121516M 063-8822118 002-90728



Project / Type

Notes

Count / Date

## Optical accessories

### OVAL LENS

| Ø (MM) | ARTICLE NUMBER(S) |
|--------|-------------------|
| 42     | 007-1965880       |



### SOFT LENS

| Ø (MM) | ARTICLE NUMBER(S) |
|--------|-------------------|
| 42     | 007-1965980       |



### WALLWASHER LENS

| Ø (MM) | ARTICLE NUMBER(S) |
|--------|-------------------|
| 42     | 007-1965780       |

