

MOVE IN 45 round

trimless

063-8121416V 063-8812117 002-90729



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Semi-Recessed _____

brushed aluminium _____

IP20 _____

406 lm _____

fixture 59 lm/W¹ _____

LED

2700 K _____

CRI ≥ 90 _____

L85 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 99 , R_r: 91 , R_{t(1-15)}: 89 _____

MR 0.54 _____

MDER 0.49 _____

Optical

super spot _____

beam angle 8° _____

PstLM ≤ 1.0² _____

SVM ≤ 0.4² _____

Electrical

DALI-2 _____

220-240 V _____

system 9.2 W _____

fixture 6.9 W _____

11 Vf _____

600 mA _____

PC2 _____

1 DALI Addr. _____

Physical

trimless _____

diameter 75 mm _____

height 106 mm _____

0.46 kg _____

Cutout

diameter 65 mm _____

min. ceiling thickness 9 mm _____


max. ceiling thickness 25 mm _____

recessed depth 195 mm _____

¹ incl. consideration of optical losses & internal control unit losses

² Value of containing product at full load (undimmed)


Light distribution



super spot 8°

h (m)	E0° (lx)	ø (m)
1	14200	0.14
2	3500	0.28
3	1600	0.41
4	900	0.55
5	600	0.69

Product drawing



Installation instructions



Lighting calculator

