

BO 55 semi-recessed

049-6140718M 002-90729



Project / Type

Notes

Count / Date



General

Ceiling , Semi-Recessed

tilt max 90°

rotation 350°

black , RAL 9005 ¹

IP20

1900 lm

fixture 90 lm/W²

LED

3500 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 97 , R_r: 90 , R₍₁₋₅₎: 89

MR 0.7

MDER 0.63

Optical

medium

beam angle 31°

PstLM ≤ 1.0 ³

SVM ≤ 0.4 ³

Electrical

DALI-2

220-240 V

system 24.7 W

fixture 21.0 W

36 Vf

600 mA

PC2

1 DALI Addr.

Physical

diameter 55 mm

height 159 mm

0.48 kg

Cutout

diameter 46 mm


min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 150 mm

Cylindrical spotlight in aluminium; surface black powder coated; 350° rotatable and 90° tiltable; recessed version with trim; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3500 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality, aluminium, vapour deposition coated reflector with faceted lens design; precise radiation characteristic with 31° beam; good glare control through recessed light point level; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC2; 220-240 V; incl. DALI-2 converter; flicker-free visual comfort through analogue current control (minimum value 1%); external converter for ceiling insertion, through-wiring suitable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



medium 31°			
h (m)	EO° (lx)	ø (m)	
1	6860	0.55	
2	1710	1.10	
3	760	1.65	
4	430	2.20	
5	270	2.75	

Product drawing



¹ RAL code
² FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.
³ Value of containing product at full load (undimmed)

Installation instructions

Lighting calculator