

INDIRECT EXTENSION

high power MOVE IT PRO

086-6805530B



Project / Type

Notes

Count / Date



Linear light inset made of plastic; light inset can be installed flexibly and without tools; flush with profile system; power supplied via INDIRECT MOVE IT PRO inset; with indirect light component for additional accentuation of the ceiling; high quality lens system for maximum, homogeneous ceiling illumination; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3; light source replaceable by an authorized professional;

Light distribution



Product drawing



General

Ceiling , Track Suspended

indirect extension high power

white

IP20

747 lm

LED

3000 K

CRI ≥ 80

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.56

MDER 0.51

Optical

UGR < 10 , $\geq 65^\circ$ < 1500 cd/m²

Electrical

system 5.5 W

inset 4.7 W

50 mA

PC3

system 136 lm/W¹

Physical

length 245 mm

width 24 mm

height 6 mm

¹ incl. optical losses and the efficiency of the operating device (converter)

Installation instructions



Lighting calculator



INDIRECT EXTENSION

high power MOVE IT PRO

086-6805530B



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.96	0.94	0.92	0.9
LSF	1	1	1	1	1

MF

MF

LMF^a

LMF × RSMF × LLMF × LSF

Maintenance Factor

Luminaire Maintenance Factor

RSMF^a

LLMF

LSF

Room Surface Maintenance Factor

Lamp Lumens Maintenance Factor

Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

