

INDIRECT EXTENSION

low power MOVE IT PRO

086-6800630B



Project / Type


Notes

Count / Date



Linear light inset made of plastic; light inset can be installed flexibly and without tools; flush with profile system; power supplied via INDIRECT MOVE IT PRO inset; with indirect light component for additional accentuation of the ceiling; high quality lens system for maximum, homogeneous ceiling illumination; passive cooling of the LEDs through improved heat sink geometry; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3; light source replaceable by an authorized professional;

Light distribution



Product drawing



III

X-PERT

UGR

cd/m²

CRI

General

Ceiling , Track Suspended

indirect extension low power

white

IP20

425 lm

LED

4000 K

CRI ≥ 80

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.72

MDER 0.65

Optical

UGR < 10 , $\geq 65^\circ$ < 1500 cd/m²

Electrical

2.8 W

inset 2.4 W

50 mA

PC3

152 lm/W

Physical

length 245 mm

width 24 mm

height 6 mm

Installation instructions



Lighting calculator

