

# INDIRECT EXTENSION

## low power MOVE IT PRO

086-6800630B



Project / Type	
Notes	
Count / Date	



Linear light inset made of plastic; light inset can be installed flexibly and without tools; flush with profile system; power supplied via INDIRECT MOVE IT PRO inset; with indirect light component for additional accentuation of the ceiling; high quality lens system for maximum, homogeneous ceiling illumination; passive cooling of the LEDs through improved heat sink geometry; light colour 4000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 80$ ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3; light source replaceable by an authorized professional;

### Light distribution



### Product drawing



### General

Ceiling , Track Suspended
indirect extension low power
white
IP20
425 lm

### LED

4000 K
CRI $\geq 80$
L90 / 50000 h
initial MacAdam $\leq 3$ SDCM
MR 0.72
MDER 0.65

### Optical

UGR $< 10$ , $\geq 65^\circ$ $< 1500$ cd/m <sup>2</sup>
---

### Electrical

system 2.8 W
inset 2.4 W
50 mA
PC3
system 152 lm/W <sup>1</sup>

### Physical

length 245 mm
width 24 mm
height 6 mm

<sup>1</sup> incl. optical losses and the efficiency of the operating device (converter)

### Installation instructions



### Lighting calculator

