

INDIRECT EXTENSION

low power MOVE IT PRO

086-6800430B



Project / Type	
Notes	
Count / Date	



Linear light inset made of plastic; light inset can be installed flexibly and without tools; flush with profile system; power supplied via INDIRECT MOVE IT PRO inset; with indirect light component for additional accentuation of the ceiling; high quality lens system for maximum, homogeneous ceiling illumination; passive cooling of the LEDs through improved heat sink geometry; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3; light source replaceable by an authorized professional;

Light distribution



Product drawing



General

Ceiling , Track Suspended
indirect extension low power
white
IP20
374 lm

LED

2700 K
CRI ≥ 80
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
MR 0.48
MDER 0.44

Optical

UGR < 10 , $\geq 65^\circ$ < 1500 cd/m ²

Electrical

system 2.8 W
inset 2.4 W
50 mA
PC3
system 134 lm/W ¹

Physical

length 245 mm
width 24 mm
height 6 mm

¹ incl. optical losses and the efficiency of the operating device (converter)

Installation instructions



Lighting calculator

