

VARO 110 S

180-6531237S



Project / Type	
Notes	
Count / Date	



--	--	--	--

General
Ceiling , Track
tilt max 90°
rotation 355°
white , RAL9016 ¹
IP20
4500 lm

LED
3500 K
CRI ≥ 90
L85 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 97 , R _f : 90 , R ₍₁₋₁₅₎ : 93
MR 0.73
MDER 0.66


Optical
spot
beam angle 14°

Electrical
DALI-2
system 36 W
PC2 220-240V
system 125 lm/W ²

Physical
diameter 110 mm
height 110 mm


Track light made of die-cast aluminium; surface white powder coated; 355° rotatable and 90° tiltable; integrated converter in the plastic adapter; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3500 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; including high quality aluminium reflector with spherical reflector; high gloss anodised; neutral colour reflection through absolute freedom from interference colour; for brilliant object staging; precise radiation characteristic with 14° beam; installed and exchanged without tools; optical attachments available as accessories; optical attachments can be combined; accessories are listed separately; degree of protection IP20; PC2 220-240V; incl. DALI-2 converter; adapter for toolless insertion or movement on a variety of 3-phase power tracks; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



spot 14°			
h (m)	EO° (lx)	ø (m)	
1	37100	0.25	
2	9300	0.50	
3	4100	0.75	
4	2300	1.00	
5	1500	1.25	

Product drawing



¹ RAL code
² incl. optical losses and the efficiency of the operating device (converter)

Installation instructions



Lighting calculator

