

# ARY cable suspended 2 lamps

MOVE IT PRO

086-73101387M



Project / Type

Notes

Count / Date



## General

Ceiling , Track Suspended

black , RAL 9005 <sup>1</sup>

Converter Traffic White

IP20

2190 lm

## LED

4000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 96 , R<sub>r</sub>: 89 , R<sub>t(1-15)</sub>: 89

MR 0.84

MDER 0.76

## Optical

medium

beam angle 25°

PstLM ≤ 1.0<sup>2</sup> <sup>3</sup>

SVM ≤ 0.4<sup>2</sup> <sup>3</sup>

## Electrical

DALI-2

220-240 V

system 28.2 W

system 78 lm/W<sup>4</sup>

PC2

1 DALI Addr.

## Physical

cable 2000 mm


diameter 47 mm

height 110 mm

adapter 402 mm

Decorative pendant light inset made of aluminium; 2 lamps; cylindrical spotlight heads; surface black powder coated; light inset, incl. high power adapter + converter can be installed flexibly and without tools; power supplied via MOVE IT PRO system track profile; pendant fitting with 2000mm suspension, incl. feed (black), can be individually shortened; shades available as accessory in RAL colours velvet beige, madeira brown, kingfisher grey, woodpecker olive, signal white or signal black; accessories are listed separately; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 25° beam; degree of protection IP20; PC2; 220-240 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;


## Light distribution



medium 25° combined

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1     | 9470     | 0.44  |
| 2     | 2370     | 0.89  |
| 3     | 1050     | 1.33  |
| 4     | 590      | 1.78  |
| 5     | 380      | 2.22  |

## Product drawing



<sup>1</sup> RAL code <sup>2</sup> combined

<sup>3</sup> Value of containing product at full load (undimmed)

<sup>4</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

## Installation instructions

