

# NOBA 60 suspended 1 lamp

MOVE IT PRO

086-71002377W



Project / Type

Notes

Count / Date



## General

Ceiling , Track Suspended

traffic white , RAL 9016 <sup>1</sup>

Converter Traffic White

IP20

1000 lm

## LED

3500 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 97 , R<sub>f</sub>: 90 , R<sub>(1-15)</sub>: 89

MR 0.7

MDER 0.63

## Optical

wide flood

beam angle 67°

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

## Electrical

DALI-2

220-240 V

system 10.0 W

system 100 lm/W<sup>3</sup>

PC2

1 DALI Addr.

## Physical

length 60 mm

width 60 mm

height 60 mm


adapter 402 mm

suspension 2000 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

<sup>3</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

## Light distribution



wide flood 67°

h (m)	E0° (lx)	ø (m)
1	951	1.31
2	238	2.63
3	106	3.94
4	59	5.26
5	38	6.57

## Product drawing



## Installation instructions



## Lighting calculator

