

NOBA 60 suspended 1 lamp

MOVE IT PRO

086-71001388W



Project / Type

Notes

Count / Date



General

Ceiling , Track Suspended

jet black , RAL 9005 ¹

Converter Jet Black

IP20

1060 lm

LED

4000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 97 , R_f: 90 , R₍₁₋₁₅₎: 89

MR 0.81

MDER 0.74

Optical

wide flood

beam angle 67°

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrical

DALI-2

220-240 V

system 10.0 W

system 106 lm/W³

PC2

1 DALI Addr.

Physical

length 60 mm

width 60 mm

height 60 mm


adapter 402 mm

suspension 2000 mm

¹ RAL code ² Value of containing product at full load (undimmed)

³ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Light distribution



wide flood 67°

h (m)	E0° (lx)	ø (m)
1	1010	1.31
2	250	2.63
3	110	3.94
4	60	5.26
5	40	6.57

Product drawing



Installation instructions



Lighting calculator

