

NOBA 60 suspended 3 lamps

MOVE IT PRO
086-71200388W



Project / Type _____


Notes _____

Count / Date _____



Decorative pendant light inset made of aluminium; 3 lamps; surface jet black powder coated; light inset, incl. high power adapter + converter can be installed flexibly and without tools; power supplied via MOVE IT PRO system track profile; pendant fitting with 2000mm suspension, incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality plano-convex glass lens; beam angle 67°; no multiple shadows; degree of protection IP20; PC2; 220-240 V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;


Light distribution



wide flood 67° combined

h (m)	EO° (lx)	ø (m)
1	2870	1.31
2	720	2.63
3	320	3.94
4	180	5.26
5	110	6.57

Product drawing



General

Ceiling , Track Suspended
jet black , RAL 9005 ¹
Converter Jet Black
IP20
3020 lm

LED

3000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R_g: 100 , R_f: 91 , R_{f(1-15)}: 88
MR 0.59
MDER 0.53

Optical

wide flood
beam angle 67°
PstLM $\leq 1.0^2$ ³
SVM $\leq 0.4^2$ ³

Electrical

DALI-2
220-240 V
system 28.8 W
system 105 lm/W⁴
PC2
1 DALI Addr.

Physical

length 60 mm
width 60 mm
height 60 mm
adapter 402 mm
suspension 2000 mm

¹ RAL code ² combined
³ Value of containing product at full load (undimmed)
⁴ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions

