

# NOBA 60 suspended 2 lamps

MOVE IT PRO  
086-71109378W



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



**General**

Ceiling , Track Suspended \_\_\_\_\_

traffic white , RAL9016 <sup>1</sup> \_\_\_\_\_

Converter Jet Black \_\_\_\_\_

IP20 \_\_\_\_\_

1860 lm \_\_\_\_\_

**LED**

2700 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

initial MacAdam ≤ 2 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>t(1-15)</sub>: 89 \_\_\_\_\_

MR 0.53 \_\_\_\_\_

MDER 0.48 \_\_\_\_\_

**Optical**

wide flood \_\_\_\_\_

beam angle 67° \_\_\_\_\_

PstLM ≤ 1.0 <sup>2</sup> \_\_\_\_\_

SVM ≤ 0.4 <sup>2</sup> \_\_\_\_\_

**Electrical**

DALI-2 \_\_\_\_\_

19.2 W \_\_\_\_\_

PC2 220-240V \_\_\_\_\_

97 lm/W \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_

**Physical**

length 60 mm \_\_\_\_\_

width 60 mm \_\_\_\_\_


height 60 mm \_\_\_\_\_

402 (adapter) mm \_\_\_\_\_

suspension 2000 mm \_\_\_\_\_

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)


## Light distribution



wide flood 67°

h (m)	E0° (lx)	ø (m)
1	884	1.31
2	221	2.63
3	98	3.94
4	55	5.26
5	35	6.57

## Product drawing



## Lighting calculator

