

MINO 60 direct / indirect high lumen ceiling /

suspended system
046-502661XZ



Project / Type

Notes

Count / Date



RG0
IEC 62471

220-240V

X-PERT

X-PERT

General

Ceiling , Suspended

special colours

4420 lm/m

IP20

indirect 4470 lm

direct 3280 lm

total 7750 lm

LED

4000 K

CRI ≥ 80

L90 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

MR 0.72

MDER 0.65

Optical

Microprismatic

microprismatic

UGR < 19

Electrical

non DIM

system 53 W

PC1 220-240V

system 146 lm/W¹

30 W/m

Physical

length 1756 mm


width 60 mm

height 80 mm

4.6 kg

¹ incl. optical losses and the efficiency of the operating device (converter)

Light distribution



Product drawing



Installation instructions



Lighting calculator



MINO 60 direct / indirect high lumen ceiling /

suspended system
046-502661XZ



Project / Type _____

Notes _____

Count / Date _____

Maintenance Factors

| Operating Time [h] | 10 000 | 20 000 | 30 000 | 40 000 | 50 000 |
|--------------------|------------------------------|--------|-------------------|---------------------------------|--------|
| LLMF | 0.98 | 0.96 | 0.94 | 0.92 | 0.9 |
| LSF | 1 | 1 | 1 | 1 | 1 |
| MF | LMF × RSMF × LLMF × LSF | | RSMF ^a | Room Surface Maintenance Factor | |
| MF | Maintenance Factor | | LLMF | Lamp Lumens Maintenance Factor | |
| LMF ^a | Luminaire Maintenance Factor | | LSF | Lamp Survival Faktor | |

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

| Automatic Circuit Breaker Type | Number of Fixtures |
|--------------------------------|--------------------|
| B10 | 15 |
| B13 | 19 |
| B16 | 24 |
| B20 | 30 |
| C10 | 25 |
| C13 | 32 |
| C16 | 40 |
| C20 | 49 |

Mounting accessories

END CAPS

| TYPE | COLOUR | L-W-H (MM) | ARTICLE NUMBER(S) |
|--------|-----------------|------------|-------------------|
| 1 pair | traffic white | 60-40-4 | 046-5010017 |
| 1 pair | jet black | 60-40-4 | 046-5010018 |
| 1 pair | white aluminium | 60-40-4 | 046-501001G |
| 1 pair | special colours | 60-40-4 | 046-501001X |



Mounting accessories

LINEAR CONNECTOR

| TYPE | ARTICLE NUMBER(S) |
|-----------|-------------------|
| 1 piece | 005-40046 |
| 10 pieces | 005-40046.10 |



OPAL COVER LINEAR CONNECTOR

| ARTICLE NUMBER(S) |
|-------------------|
| 006-14000 |



Mounting accessories

CABLE SUSPENSION

| ARTICLE NUMBER(S) |
|-------------------|
| 005-2122110 |



CABLE RAIL

| Ø (MM) | ARTICLE NUMBER(S) |
|--------|-------------------|
| 1200 | 005-2491110 |



MINO 60 direct / indirect
high lumen ceiling /
suspended system
046-502661XZ



Project / Type

Notes

Count / Date

Electrical accessories

THROUGH WIRE

| TYPE | ARTICLE NUMBER(S) |
|-------------------------|-------------------|
| 3 x 1,5 mm² 10 pieces | 004-90003 |
| 5 x 1,5 mm² 10 pieces | 004-90005 |



Electrical accessories

CANOPY / FEEDER CABLE

| TYPE | COLOUR | L-W-H (MM) | ARTICLE NUMBER(S) |
|-------------|---------------|------------|-------------------|
| 3 x 1,5 mm² | traffic white | 90-90-22 | 005-2212317 |
| 3 x 1,5 mm² | jet black | 90-90-22 | 005-2212318 |
| 5 x 1,5 mm² | pure white | 90-90-22 | 005-2212417 |
| 5 x 1,5 mm² | jet black | 90-90-22 | 005-2212418 |

