

MINO 60 direct / indirect high lumen ceiling /

suspended system
046-502563GH



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Suspended _____

grey , RAL 9006 ¹ _____

IP20 _____

indirect 2400 lm _____

direct 3930 lm _____

total 6330 lm _____

4330 lm/m _____

LED

4000 K _____

CRI ≥ 80 _____

L90 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

MR 0.72 _____

MDER 0.65 _____

Optical

High Performance Opal _____

opal (lamberts) _____

PstLM ≤ 1.0 ² _____

SVM ≤ 0.4 ² _____

Electrical

DALI-2 _____

220-240 V _____

system 43 W _____

system 147 lm/W³ _____

PC1 _____

1 DALI Addr. _____

29 W/m _____

Physical

length 1464 mm _____


width 60 mm _____

height 80 mm _____

3.8 kg _____

¹ RAL code ² Value of containing product at full load (undimmed)
³ FIXTURE: incl. consideration of optical losses & internal control
unit losses SYSTEM: incl. consideration of optical losses,
internal control unit losses & operating device efficiency.

Light distribution



Product drawing



Installation instructions



Lighting calculator

