

# MINO 60 direct / indirect high lumen ceiling /

suspended system  
046-5025637H



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



## General

Ceiling , Suspended  
white , RAL 9010 <sup>1</sup>  
IP20  
indirect 2400 lm  
direct 3930 lm  
total 6330 lm  
4330 lm/m

## LED

4000 K  
CRI  $\geq 80$   
L90 / 50000 h  
initial MacAdam  $\leq 3$  SDCM  
MR 0.72  
MDER 0.65

## Optical

High Performance Opal  
opal (lambertsch)  
PstLM  $\leq 1.0$  <sup>2</sup>  
SVM  $\leq 0.4$  <sup>2</sup>


## Electrical

DALI-2  
220-240 V  
system 43 W  
system 147 lm/W<sup>3</sup>  
PC1  
1 DALI Addr.  
29 W/m

## Physical

length 1464 mm  
width 60 mm  
height 80 mm  
3.8 kg

## Light distribution



## Product drawing



<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

## Installation instructions



## Lighting calculator

