

MINO 60 direct / indirect high lumen ceiling /

suspended system
046-5024637Z



| | |
|----------------|--|
| Project / Type | |
| Notes | |
| Count / Date | |



General

| |
|-------------------------------|
| Ceiling , Suspended |
| white , RAL 9010 ¹ |
| IP20 |
| indirect 1920 lm |
| direct 2730 lm |
| total 4650 lm |
| 3970 lm/m |

LED

| |
|--------------------------|
| 4000 K |
| CRI ≥ 80 |
| L90 / 50000 h |
| initial MacAdam ≤ 3 SDCM |
| MR 0.72 |
| MDER 0.65 |

Optical

| |
|--------------------------|
| Microprismatic |
| microprismatic |
| UGR < 19 |
| PstLM ≤ 1.0 ² |
| SVM ≤ 0.4 ² |


Electrical

| |
|------------------------------|
| DALI-2 |
| 220-240 V |
| system 34 W |
| system 137 lm/W ³ |
| PC1 |
| 1 DALI Addr. |
| 29 W/m |

Physical

| |
|----------------|
| length 1172 mm |
| width 60 mm |
| height 80 mm |
| 3.2 kg |

Light distribution



Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)
³ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions



Lighting calculator

