

MINO 60 CURVE 45° high lumen

ceiling / suspended system

034-0952638Z



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

black , RAL9005 ¹

2210 lm/m

IP20

2600 lm

LED

4000 K

CRI ≥ 80

L90 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

MR 0.72

MDER 0.65

Optical

Microprismatic

microprismatic

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrical

DALI-2

system 22.1 W

PC1 220-240V

system 118 lm/W³

1 DALI Addr.

19 W/m

Physical

width 60 mm

height 80 mm

curve length 1178 mm

centerline radius 1500 mm


segment 45°

4 kg

¹ RAL code ² Value of containing product at full load (undimmed)

³ incl. optical losses and the efficiency of the operating device (converter)

Light distribution



Product drawing



[034-0952638Z] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

21.11.2024