

MINO 60 CURVE 45° high lumen

ceiling / suspended system
034-095051XH



| | |
|----------------|--|
| Project / Type | |
| Notes | |
| Count / Date | |



| | | | |
|------------------|----------|--------|--------|
| RG0 IEC 62471 | 220-240V | X-PERT | X-PERT |
|------------------|----------|--------|--------|

General

| |
|---------------------|
| Ceiling , Suspended |
| special colours |
| 2300 lm/m |
| IP20 |
| 1360 lm |

LED

| |
|---------------------------------|
| 3000 K |
| CRI ≥ 80 |
| L90 / 50000 h |
| photobio. safety RG 0 - no Risk |
| initial MacAdam ≤ 3 SDCM |
| MR 0.56 |
| MDER 0.51 |

Optical

| |
|--------------------------|
| High Performance Opal |
| opal (lambertsch) |
| PstLM ≤ 1.0 ¹ |
| SVM ≤ 0.4 ¹ |

Electrical

| |
|------------------------------|
| non DIM |
| system 11.9 W |
| PC1 220-240V |
| system 114 lm/W ² |
| 20 W/m |

Physical

| |
|--------------------------|
| width 60 mm |
| height 80 mm |
| curve length 589 mm |
| centerline radius 750 mm |
| segment 45° |
| 1.6 kg |

Circular segment of rolled aluminium profile, angular design, seamlessly welded; CURVE segment design 45°; for continuous lighting systems; light tight final end caps made of aluminium (available as an accessory); no visible screws; surface special colours powder coated; for ceiling surface mounting or suspended mounting (1500 mm cable suspension as an accessory); with integrated toolless suspension height adjustment on the luminaire; spring clip attachment to the luminaire; freely positionable; luminaire profile for mounting available in advance; remaining lamp components mounted without tools; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; HPO (High Performance Opal) cover for uniform illumination; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; internal wiring in light halogen free; incl. converter, non dimmable; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ Value of containing product at full load (undimmed)
² incl. optical losses and the efficiency of the operating device (converter)

Installation instructions



Lighting calculator

