

# MINO 60 CURVE 90° mid lumen

ceiling / suspended system  
034-094551XH



|                |  |
|----------------|--|
| Project / Type |  |
| Notes          |  |
| Count / Date   |  |



## General

|                     |  |
|---------------------|--|
| Ceiling , Suspended |  |
| special colours     |  |
| IP20                |  |
| 1230 lm             |  |
| 1580 lm/m           |  |

## LED

|                          |  |
|--------------------------|--|
| 3000 K                   |  |
| CRI ≥ 80                 |  |
| L90 / 50000 h            |  |
| initial MacAdam ≤ 3 SDCM |  |
| MR 0.56                  |  |
| MDER 0.51                |  |

## Optical

|                          |  |
|--------------------------|--|
| High Performance Opal    |  |
| opal (lambertsch)        |  |
| PstLM ≤ 1.0 <sup>1</sup> |  |
| SVM ≤ 0.4 <sup>1</sup>   |  |

## Electrical


|                              |  |
|------------------------------|--|
| non DIM                      |  |
| 220-240 V                    |  |
| system 10.4 W                |  |
| system 118 lm/W <sup>2</sup> |  |
| PC1                          |  |
| 13 W/m                       |  |

## Physical

|                          |  |
|--------------------------|--|
| width 60 mm              |  |
| height 80 mm             |  |
| curve length 785 mm      |  |
| centerline radius 500 mm |  |
| segment 90°              |  |
| 1.8 kg                   |  |

Circular segment of rolled aluminium profile, angular design, seamlessly welded; CURVE segment design 90°; for continuous lighting systems; light tight final end caps made of aluminium (available as an accessory); no visible screws; surface special colours powder coated; for ceiling surface mounting or suspended mounting (1500 mm cable suspension as an accessory); with integrated toolless suspension height adjustment on the luminaire; spring clip attachment to the luminaire; freely positionable; luminaire profile for mounting available in advance; remaining lamp components mounted without tools; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; HPO (High Performance Opal) cover for uniform illumination; degree of protection IP20; PC1; 220-240 V; internal wiring in light halogen free; incl. converter, non dimmable; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



<sup>1</sup> Value of containing product at full load (undimmed)  
<sup>2</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

## Installation instructions



## Lighting calculator

