

# FRAME 60 high lumen

trim system

007-93M9637 006-16302G 035-03037



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



220-240V X-PERT UGR ≤22 CRI ≥80 DALI-2 1ADDR. X-PERT

## General

Ceiling , Recessed  
white , RAL9016 <sup>1</sup>  
2360 lm/m  
IP20  
7060 lm

## LED

4000 K  
CRI ≥ 80  
L90 / 50000 h  
photobio. safety RG 0 - no Risk  
initial MacAdam ≤ 3 SDCM  
MR 0.72  
MDER 0.65

## Optical

Microprismatic  
microprismatic  
PstLM ≤ 1.0 <sup>2</sup>  
SVM ≤ 0.4 <sup>2</sup>

## Electrical

DALI-2  
58 W  
PC1 220-240V  
122 lm/W  
1 DALI Addr.  
19 W/m

## Physical


trim  
length 3000 mm  
width 77 mm  
height 78 mm  
7.3 kg

## Cutout

length 3016 mm  
width 66 mm  
min. ceiling thickness 8 mm  
max. ceiling thickness 25 mm  
recessed depth 108 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

## Light distribution



## Product drawing

