

# FRAME 60 high lumen

trim system

007-93M8037 006-16232H 035-02537



Project / Type

Notes

Count / Date



## General

Ceiling , Recessed

white , RAL9016 <sup>1</sup>

IP20

4770 lm

2030 lm/m

## LED

3000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>t(1-15)</sub>: 89

MR 0.61

MDER 0.55

## Optical

High Performance Opal

opal (lambertsch)

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

## Electrical

DALI-2

220-240 V

system 45 W

PC1

system 106 lm/W<sup>3</sup>

1 DALI Addr.

19 W/m

## Physical

trim

length 2344 mm

width 77 mm

height 78 mm

5.3 kg

## Cutout

length 2360 mm

width 66 mm


min. ceiling thickness 8 mm

max. ceiling thickness 25 mm


recessed depth 108 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> incl. optical losses and the efficiency of the operating device (converter)

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator



# FRAME 60 high lumen

trim system

007-93M8037 006-16232H 035-02537



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_

## Maintenance Factors

| Operating Time [h] | 10 000                       | 20 000 | 30 000  | 40 000 | 50 000 |
|--------------------|------------------------------|--------|---|--------|--------|
| LLMF               | 0.98                         | 0.96   | 0.94  | 0.92   | 0.9    |
| LSF                | 1                            | 1      | 1   | 1      | 1      |
| MF                 | LMF × RSMF × LLMF × LSF      |        | RSMF <sup>a</sup> Room Surface Maintenance Factor |        |        |
| MF                 | Maintenance Factor           |        | LLMF Lamp Lumens Maintenance Factor               |        |        |
| LMF <sup>a</sup>   | Luminaire Maintenance Factor |        | LSF Lamp Survival Faktor                          |        |        |

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Circuit Breaker Types

| Automatic Circuit Breaker Type | Number of Fixtures |
|--------------------------------|--------------------|
| B10                            | 7                  |
| B13                            | 10                 |
| B16                            | 12                 |
| B20                            | 14                 |
| C10                            | 10                 |
| C13                            | 20                 |
| C16                            | 24                 |
| C20                            | 28                 |

## Components

### LIGHT OPTIC COVER

| TYPE                  | ARTICLE NUMBER(S) |
|-----------------------|-------------------|
| opal high performance | 006-16232H        |

### INSTALLATION CHANNEL

| TYPE    | COLOUR        | L-W-H (MM) | ARTICLE NUMBER(S) |
|---------|---------------|------------|-------------------|
| 2344 mm | traffic white | 2344-77-76 | 035-02537         |



## Mounting accessories

### END CAPS

| TYPE   | COLOUR          | ARTICLE NUMBER(S) |
|--------|-----------------|-------------------|
| 1 pair | traffic white   | 035-13137         |
| 1 pair | white aluminium | 035-1313G         |



## Mounting accessories

### LINEAR CONNECTOR

| TYPE      | ARTICLE NUMBER(S) |
|-----------|-------------------|
| 1 piece   | 005-40046         |
| 10 pieces | 005-40046:10      |



### OPAL COVER LINEAR CONNECTOR

| ARTICLE NUMBER(S) |
|-------------------|
| 006-14000         |



# FRAME 60 high lumen

trim system

007-93M8037 006-16232H 035-02537



Project / Type

Notes

Count / Date

## Mounting accessories

### MOUNTING BRACKET

| TYPE      | ARTICLE NUMBER(S) |
|-----------|-------------------|
| 1 piece   | 035-10200         |
| 25 pieces | 035-10200.25      |



## Electrical accessories

### THROUGH WIRE

| TYPE                                | ARTICLE NUMBER(S) |
|-------------------------------------|-------------------|
| 3 x 1,5 mm <sup>2</sup>   10 pieces | 004-90003         |
| 5 x 1,5 mm <sup>2</sup>   10 pieces | 004-90005         |

