

MINO 60 high lumen

ceiling / suspended system

007-93M5637 006-16152Z 046-400501X



| | |
|----------------|--|
| Project / Type | |
| Notes | |
| Count / Date | |



General

| | |
|---------------------|--|
| Ceiling , Suspended | |
| special colours | |
| IP20 | |
| 3420 lm | |
| 2320 lm/m | |

LED

| | |
|--------------------------|--|
| 4000 K | |
| CRI ≥ 80 | |
| L90 / 50000 h | |
| initial MacAdam ≤ 3 SDCM | |
| MR 0.72 | |
| MDER 0.65 | |

Optical

| | |
|--------------------------|--|
| Microprismatic | |
| microprismatic | |
| PstLM ≤ 1.0 ¹ | |
| SVM ≤ 0.4 ¹ | |

Electrical


| | |
|------------------------------|--|
| DALI-2 | |
| 220-240 V | |
| system 29.1 W | |
| system 118 lm/W ² | |
| PC1 | |
| 1 DALI Addr. | |
| 20 W/m | |

Physical

| | |
|----------------|--|
| trim | |
| length 1472 mm | |
| width 60 mm | |
| height 80 mm | |
| 3.8 kg | |

Luminaire housing made of extruded aluminium profile; angular design; for continuous lighting systems; light tight final end caps made of aluminium (available as an accessory); no visible screws; surface special colours powder coated; for ceiling surface mounting or suspended mounting (1500 mm cable suspension as an accessory); with integrated toolless suspension height adjustment on the luminaire; spring clip attachment to the luminaire; freely positionable; luminaire profile for mounting available in advance; remaining lamp components mounted without tools; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; micro prismatic PMMA diffuser incl. diffuser film for homogeneous illumination and reduced luminance; degree of protection IP20; PC1; 220-240 V; internal wiring in light halogen free; incl. DALI-2 converter; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ Value of containing product at full load (undimmed)
² FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions



Lighting calculator

