

FRAME 60 high lumen

trim system

007-93M8637 006-16232H 035-02537



| | |
|----------------|--|
| Project / Type | |
| Notes | |
| Count / Date | |



General

| |
|-------------------------------|
| Ceiling , Recessed |
| white , RAL 9016 ¹ |
| IP20 |
| 6290 lm |
| 2680 lm/m |

LED

| |
|--------------------------|
| 4000 K |
| CRI ≥ 80 |
| L90 / 50000 h |
| initial MacAdam ≤ 3 SDCM |
| MR 0.72 |
| MDER 0.65 |

Optical

| |
|--------------------------|
| High Performance Opal |
| opal (lambersch) |
| PstLM ≤ 1.0 ² |
| SVM ≤ 0.4 ² |

Electrical

| |
|------------------------------|
| DALI-2 |
| 220-240 V |
| system 45 W |
| system 140 lm/W ³ |
| PC1 |
| 1 DALI Addr. |
| 19 W/m |


Physical

| |
|----------------|
| trim |
| length 2344 mm |
| width 77 mm |
| height 78 mm |
| 5.3 kg |

Cutout

| |
|-----------------------------|
| length 2360 mm |
| width 66 mm |
| min. ceiling thickness 8 mm |
| max. ceiling thickness 8 mm |
| recessed depth 108 mm |

Light distribution



Product drawing

