

MINO 60 high lumen

ceiling / suspended system

007-93M8137 006-16232H 046-4008017



Project / Type

Notes

Count / Date



RG0
IEC 62471

220-240V

X-PERT

X-PERT

General

Ceiling , Suspended

white , RAL9010 ¹

2200 lm/m

IP20

5150 lm

LED

4000 K

CRI ≥ 90

L90 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

R_g: 99 , R_f: 92 , R₍₁₋₁₅₎: 90

MR 0.81

MDER 0.74

Optical

High Performance Opal

opal (lambertsch)

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Luminaire housing made of extruded aluminium profile; angular design; for continuous lighting systems; light tight final end caps made of aluminium (available as an accessory); no visible screws; surface white powder coated; for ceiling surface mounting or suspended mounting (1500 mm cable suspension as an accessory); with integrated toolless suspension height adjustment on the luminaire; spring clip attachment to the luminaire; freely positionable; luminaire profile for mounting available in advance; remaining lamp components mounted without tools; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; HPO (High Performance Opal) cover for uniform illumination; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; internal wiring in light halogen free; incl. DALI-2 converter; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Electrical

DALI-2

system 45 W

PC1 220-240V

system 114 lm/W³

1 DALI Addr.

19 W/m

Physical

trim


length 2344 mm

width 60 mm

height 80 mm

5.5 kg

Light distribution



Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. optical losses and the efficiency of the operating device (converter)

Installation instructions



Lighting calculator



MINO 60 high lumen

ceiling / suspended system

007-93M8137 006-16232H 046-4008017



Project / Type _____

Notes _____

Count / Date _____

Maintenance Factors

| Operating Time [h] | 10 000 | 20 000 | 30 000 | 40 000 | 50 000 |
|--------------------|------------------------------|--------|-------------------|---------------------------------|--------|
| LLMF | 0.98 | 0.96 | 0.94 | 0.92 | 0.9 |
| LSF | 1 | 1 | 1 | 1 | 1 |
| MF | LMF × RSMF × LLMF × LSF | | RSMF ^a | Room Surface Maintenance Factor | |
| MF | Maintenance Factor | | LLMF | Lamp Lumens Maintenance Factor | |
| LMF ^a | Luminaire Maintenance Factor | | LSF | Lamp Survival Faktor | |

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

| Automatic Circuit Breaker Type | Number of Fixtures |
|--------------------------------|--------------------|
| B10 | 7 |
| B13 | 10 |
| B16 | 12 |
| B20 | 14 |
| C10 | 10 |
| C13 | 20 |
| C16 | 24 |
| C20 | 28 |

Components

LIGHT OPTIC COVER

| TYPE | ARTICLE NUMBER(S) |
|-----------------------|-------------------|
| opal high performance | 006-16232H |

INSTALLATION CHANNEL

| TYPE | COLOUR | L-W-H (MM) | ARTICLE NUMBER(S) |
|---------|------------|------------|-------------------|
| 2344 mm | pure white | 2344-60-80 | 046-4008017 |



Mounting accessories

END CAPS

| TYPE | COLOUR | L-W-H (MM) | ARTICLE NUMBER(S) |
|--------|-----------------|------------|-------------------|
| 1 pair | traffic white | 60-40-4 | 046-5010017 |
| 1 pair | jet black | 60-40-4 | 046-5010018 |
| 1 pair | white aluminium | 60-40-4 | 046-501001G |
| 1 pair | special colours | 60-40-4 | 046-501001X |



Mounting accessories

LINEAR CONNECTOR

| TYPE | ARTICLE NUMBER(S) |
|-----------|-------------------|
| 1 piece | 005-40046 |
| 10 pieces | 005-40046.10 |



OPAL COVER LINEAR CONNECTOR

| ARTICLE NUMBER(S) |
|-------------------|
| 006-14000 |



MINO 60 high lumen

ceiling / suspended system

007-93M8137 006-16232H 046-4008017



Project / Type

Notes

Count / Date

Mounting accessories

CEILING CLIP

| COLOUR | ARTICLE NUMBER(S) |
|-------------|-------------------|
| transparent | 034-11636 |



Mounting accessories

CABLE SUSPENSION

| ARTICLE NUMBER(S) |
|-------------------|
| 005-2122110 |



CABLE RAIL

| Ø (MM) | ARTICLE NUMBER(S) |
|--------|-------------------|
| 1200 | 005-2491110 |



Electrical accessories

THROUGH WIRE

| TYPE | ARTICLE NUMBER(S) |
|-------------------------------------|-------------------|
| 3 x 1,5 mm ² 10 pieces | 004-90003 |
| 5 x 1,5 mm ² 10 pieces | 004-90005 |



Electrical accessories

CANOPY / FEEDER CABLE

| TYPE | COLOUR | L-W-H (MM) | ARTICLE NUMBER(S) |
|-------------------------|---------------|------------|-------------------|
| 3 x 1,5 mm ² | traffic white | 90-90-22 | 005-2212317 |
| 3 x 1,5 mm ² | jet black | 90-90-22 | 005-2212318 |
| 5 x 1,5 mm ² | pure white | 90-90-22 | 005-2212417 |
| 5 x 1,5 mm ² | jet black | 90-90-22 | 005-2212418 |

