

MINO 60 high lumen

ceiling / suspended system

007-93M3117 006-16092Z 046-4003018



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

black , RAL 9005 ¹

IP20

1680 lm

1920 lm/m

LED

4000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 99 , R_r: 92 , R_{t(1-15)}: 90

MR 0.81

MDER 0.74

Optical

Microprismatic

microprismatic

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrical

non DIM

220-240 V

system 17.5 W

system 96 lm/W³

PC1

20 W/m

Physical

trim

length 872 mm


width 60 mm

height 80 mm

2.29 kg

Luminaire housing made of extruded aluminium profile; angular design; for continuous lighting systems; light tight final end caps made of aluminium (available as an accessory); no visible screws; surface black powder coated; for ceiling surface mounting or suspended mounting (1500 mm cable suspension as an accessory); with integrated toolless suspension height adjustment on the luminaire; spring clip attachment to the luminaire; freely positionable; luminaire profile for mounting available in advance; remaining lamp components mounted without tools; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; micro prismatic PMMA diffuser incl. diffuser film for homogeneous illumination and reduced luminance; degree of protection IP20; PC1; 220-240 V; internal wiring in light halogen free; incl. converter, non dimmable; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)
³ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions



Lighting calculator



MINO 60 high lumen

ceiling / suspended system

007-93M3117 006-16092Z 046-4003018



Project / Type _____

Notes _____

Count / Date _____

Maintenance Factors

| Operating Time [h] | 10 000 | 20 000 | 30 000 | 40 000 | 50 000 |
|--------------------|------------------------------|--------|-------------------|---------------------------------|--------|
| LLMF | 0.98 | 0.96 | 0.94 | 0.92 | 0.9 |
| LSF | 1 | 1 | 1 | 1 | 1 |
| MF | LMF × RSMF × LLMF × LSF | | RSMF ^a | Room Surface Maintenance Factor | |
| MF | Maintenance Factor | | LLMF | Lamp Lumens Maintenance Factor | |
| LMF ^a | Luminaire Maintenance Factor | | LSF | Lamp Survival Faktor | |

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

| Automatic Circuit Breaker Type | Number of Fixtures |
|--------------------------------|--------------------|
| B10 | 9 |
| B13 | 13 |
| B16 | 15 |
| B20 | 18 |
| C10 | 18 |
| C13 | 26 |
| C16 | 30 |
| C20 | 36 |

Components

LIGHT OPTIC COVER

| TYPE | ARTICLE NUMBER(S) |
|----------------|-------------------|
| microprismatic | 006-16092Z |

INSTALLATION CHANNEL

| COLOUR | L-W-H (MM) | ARTICLE NUMBER(S) |
|-----------|------------|-------------------|
| jet black | 872-60-80 | 046-4003018 |

Mounting accessories

END CAPS

| TYPE | COLOUR | L-W-H (MM) | ARTICLE NUMBER(S) |
|--------|-----------------|------------|-------------------|
| 1 pair | traffic white | 60-40-4 | 046-5010017 |
| 1 pair | jet black | 60-40-4 | 046-5010018 |
| 1 pair | white aluminium | 60-40-4 | 046-501001G |
| 1 pair | special colours | 60-40-4 | 046-501001X |

Mounting accessories

LINEAR CONNECTOR

| TYPE | ARTICLE NUMBER(S) |
|-----------|-------------------|
| 1 piece | 005-40046 |
| 10 pieces | 005-40046.10 |

OPAL COVER LINEAR CONNECTOR

| ARTICLE NUMBER(S) |
|-------------------|
| 006-14000 |



MINO 60 high lumen

ceiling / suspended system

007-93M3117 006-16092Z 046-4003018



Project / Type

Notes

Count / Date

Mounting accessories

CEILING CLIP

| COLOUR | ARTICLE NUMBER(S) |
|-------------|-------------------|
| transparent | 034-11636 |



Mounting accessories

CABLE SUSPENSION

| ARTICLE NUMBER(S) |
|-------------------|
| 005-2122110 |



CABLE RAIL

| Ø (MM) | ARTICLE NUMBER(S) |
|--------|-------------------|
| 1200 | 005-2491110 |



Electrical accessories

THROUGH WIRE

| TYPE | ARTICLE NUMBER(S) |
|-------------------------|-------------------|
| 3 x 1,5 mm² 10 pieces | 004-90003 |
| 5 x 1,5 mm² 10 pieces | 004-90005 |



Electrical accessories

CANOPY / FEEDER CABLE

| TYPE | COLOUR | L-W-H (MM) | ARTICLE NUMBER(S) |
|-------------|---------------|------------|-------------------|
| 3 x 1,5 mm² | traffic white | 90-90-22 | 005-2212317 |
| 3 x 1,5 mm² | jet black | 90-90-22 | 005-2212318 |
| 5 x 1,5 mm² | pure white | 90-90-22 | 005-2212417 |
| 5 x 1,5 mm² | jet black | 90-90-22 | 005-2212418 |

