

MINO 60 high lumen

ceiling / suspended system

007-93M4037 006-16122H 046-400401G



| | |
|----------------|--|
| Project / Type | |
| Notes | |
| Count / Date | |



General

| |
|------------------------------|
| Ceiling , Suspended |
| grey , RAL 9006 ¹ |
| IP20 |
| 2380 lm |
| 2030 lm/m |

LED

| |
|---|
| 3000 K |
| CRI ≥ 90 |
| L90 / 50000 h |
| initial MacAdam ≤ 3 SDCM |
| R _g : 99 , R _r : 91 , R _{t(1-15)} : 89 |
| MR 0.61 |
| MDER 0.55 |

Optical

| |
|--------------------------|
| High Performance Opal |
| opal (lambertsch) |
| PstLM ≤ 1.0 ² |
| SVM ≤ 0.4 ² |

Electrical


| |
|------------------------------|
| DALI-2 |
| 220-240 V |
| system 23.3 W |
| system 102 lm/W ³ |
| PC1 |
| 1 DALI Addr. |
| 20 W/m |

Physical

| |
|----------------|
| trim |
| length 1172 mm |
| width 60 mm |
| height 80 mm |
| 2.87 kg |

¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. consideration of optical losses, internal control unit losses
& operating device efficiency

Light distribution



Product drawing



Installation instructions



Lighting calculator

