

FRAME 60 high lumen

trim system

007-93M2537 006-16062G 035-00637



Project / Type	
Notes	
Count / Date	



General

Ceiling , Recessed	
white , RAL 9016 ¹	
IP20	
1200 lm	
2100 lm/m	

LED

3000 K	
CRI ≥ 80	
L90 / 50000 h	
initial MacAdam ≤ 3 SDCM	
MR 0.56	
MDER 0.51	

Optical

Microprismatic	
microprismatic	
PstLM ≤ 1.0 ²	
SVM ≤ 0.4 ²	

Electrical

DALI-2	
220-240 V	
system 12.1 W	
system 99 lm/W ³	
PC1	
1 DALI Addr.	
21 W/m	

Physical


trim	
length 572 mm	
width 77 mm	
height 78 mm	
1.6 kg	

Cutout

length 588 mm	
width 66 mm	
min. ceiling thickness 8 mm	
max. ceiling thickness 25 mm	
recessed depth 108 mm	

Luminaire housing made of extruded aluminium profile; recessed light with wrap around edge; for continuous lighting systems; suitable for ceiling thickness of 8-25 mm; surface white powder coated; luminaire profile for mounting available in advance; remaining lamp components mounted without tools; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; micro prismatic PMMA diffuser incl. diffuser film for homogeneous illumination and reduced luminance; degree of protection IP20; PC1; 220-240 V; internal wiring in light halogen free; incl. DALI-2 converter; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Installation instructions



Lighting calculator

