

# FRAME 60 high lumen

trim system

007-93M2137 006-16062Z 035-0063G



Project / Type

Notes

Count / Date



220-240V

X-PERT

UGR  
≤22

CRI  
≥90

DALI-2  
1ADDR.

X-PERT

### General

Ceiling , Recessed

grey , RAL9006 <sup>1</sup>

1960 lm/m

IP20

1120 lm

### LED

4000 K

CRI ≥ 90

L90 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 99 , R<sub>f</sub>: 92 , R<sub>(1-15)</sub>: 90

MR 0.81

MDER 0.74

### Optical

Microprismatic

microprismatic

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

### Electrical

DALI-2

12.1 W

PC1 220-240V

93 lm/W

1 DALI Addr.

21 W/m

### Physical

trim

length 572 mm

width 77 mm

height 78 mm

1.6 kg

### Cutout

length 588 mm

width 66 mm


min. ceiling thickness 8 mm

max. ceiling thickness 25 mm

recessed depth 108 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

### Light distribution



### Product drawing



### Installation instructions



### Lighting calculator

