

MINO 60 mid lumen

ceiling / suspended system

007-93L5117 006-16152Z 046-400501G



Project / Type	
Notes	
Count / Date	



General

Ceiling , Suspended	
grey , RAL9006 ¹	
1130 lm/m	
IP20	
1660 lm	

LED

4000 K	
CRI ≥ 90	
L90 / 50000 h	
photobio. safety RG 0 - no Risk	
initial MacAdam ≤ 3 SDCM	
R _g : 99 , R _f : 92 , R ₍₁₋₁₅₎ : 90	
MR 0.81	
MDER 0.74	

Optical

Microprismatic	
PstLM ≤ 1.0 ²	

Electrical

non DIM	
16.6 W	
PC1 220-240V	
100 lm/W	
11 W/m	

Physical

trim	
length 1472 mm	
width 60 mm	
height 80 mm	
3.8 kg	

Luminaire housing made of extruded aluminium profile; angular design; for continuous lighting systems; light tight final end caps made of aluminium (available as an accessory); no visible screws; surface grey powder coated; for ceiling surface mounting or suspended mounting (1500 mm cable suspension as an accessory); with integrated tool-less suspension height adjustment; spring clip attachment to the luminaire; freely positionable; luminaire profile for mounting available in advance; remaining lamp components mounted without tools; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; micro prismatic PMMA diffuser incl. diffuser film for homogeneous illumination and reduced luminance; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; internal wiring in light halogen free; incl. converter, non dimmable; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

