

# FRAME 60 mid lumen

trim system

007-93L9017 006-16302H 035-03037



Project / Type

Notes

Count / Date



### General

Ceiling , Recessed

white , RAL9016 <sup>1</sup>

1220 lm/m

IP20

3650 lm

### LED

3000 K

CRI ≥ 90

L90 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89

MR 0.61

MDER 0.55

### Optical

High Performance Opal

PstLM ≤ 1.0 <sup>2</sup>

### Electrical

non DIM

33 W

PC1 220-240V

111 lm/W

11 W/m

### Physical

trim

length 3000 mm

width 77 mm

height 78 mm

6.8 kg

### Cutout

length 3016 mm

width 66 mm


min. ceiling thickness 8 mm

max. ceiling thickness 25 mm

recessed depth 108 mm

Luminaire housing made of extruded aluminium profile; recessed light with wrap around edge; for continuous lighting systems; suitable for ceiling thickness of 8-25 mm; surface white powder coated; luminaire profile for mounting available in advance; remaining lamp components mounted without tools; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; HPO (High Performance Opal) cover for uniform illumination; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; internal wiring in light halogen free; incl. converter, non dimmable; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

### Light distribution



### Product drawing



<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

### Installation instructions



### Lighting calculator



# FRAME 60 mid lumen

trim system

007-93L9017 006-16302H 035-03037



Project / Type

Notes

Count / Date

## Maintenance Factors

| Operating Time [h] | 10 000                       | 20 000 | 30 000  | 40 000 | 50 000 |
|--------------------|------------------------------|--------|---|--------|--------|
| LLMF               | 0.98                         | 0.96   | 0.94  | 0.92   | 0.9    |
| LSF                | 1                            | 1      | 1   | 1      | 1      |
| MF                 | LMF × RSMF × LLMF × LSF      |        | RSMF <sup>a</sup> Room Surface Maintenance Factor |        |        |
| MF                 | Maintenance Factor           |        | LLMF Lamp Lumens Maintenance Factor               |        |        |
| LMF <sup>a</sup>   | Luminaire Maintenance Factor |        | LSF Lamp Survival Faktor                          |        |        |

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Circuit Breaker Types

| Automatic Circuit Breaker Type | Number of Fixtures |
|--------------------------------|--------------------|
| B10                            | 15                 |
| B13                            | 19                 |
| B16                            | 24                 |
| B20                            | 30                 |
| C10                            | 25                 |
| C13                            | 32                 |
| C16                            | 40                 |
| C20                            | 49                 |

## Mounting accessories

### END CAPS

| TYPE   | COLOUR          | ARTICLE NUMBER(S) |
|--------|-----------------|-------------------|
| 1 pair | traffic white   | 035-13137         |
| 1 pair | white aluminium | 035-1313G         |



## Mounting accessories

### LINEAR CONNECTOR

| TYPE      | ARTICLE NUMBER(S) |
|-----------|-------------------|
| 1 piece   | 005-40046         |
| 10 pieces | 005-40046.10      |



### OPAL COVER LINEAR CONNECTOR

| ARTICLE NUMBER(S) |
|-------------------|
| 006-14000         |



## Mounting accessories

### MOUNTING BRACKET

| TYPE      | ARTICLE NUMBER(S) |
|-----------|-------------------|
| 1 piece   | 035-10200         |
| 25 pieces | 035-10200.25      |



## Electrical accessories

### THROUGH WIRE

| TYPE                                | ARTICLE NUMBER(S) |
|-------------------------------------|-------------------|
| 3 x 1,5 mm <sup>2</sup>   10 pieces | 004-90003         |
| 5 x 1,5 mm <sup>2</sup>   10 pieces | 004-90005         |

