

# FRAME 60 high lumen

trim system

007-9338D37 006-16232G 035-02537



Project / Type	
Notes	
Count / Date	



## General

Ceiling , Recessed
white , RAL 9016 <sup>1</sup>
IP20
5240 lm
2230 lm/m

## LED

tunable white
2700 K - 6500 K
CRI ≥ 80
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
MR 0.48
MDER 0.44

## Optical

Microprismatic
microprismatic
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>

## Electrical

DALI-2 DT8
220-240 V
system 49 W
system 107 lm/W <sup>3</sup>
PC1
1 DALI Addr.
21 W/m


## Physical

length 2344 mm
width 77 mm
height 78 mm
5.8 kg


## Cutout

length 2360 mm
width 66 mm
min. ceiling thickness 8 mm
max. ceiling thickness 8 mm
recessed depth 108 mm

## Light distribution



## Product drawing



<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

## Installation instructions



## Lighting calculator

