

NOBA 60 suspended 1 lamp

MOVE IT PRO
086-71000357W



Project / Type

Notes

Count / Date



General

Ceiling , Track Suspended

gun metal

Converter Traffic White

IP20

1010 lm

LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 100 , R_f: 91 , R₍₁₋₁₅₎: 88

MR 0.59

MDER 0.53

Optical

wide flood

beam angle 67°

PstLM ≤ 1.0 ¹

SVM ≤ 0.4 ¹

Electrical

DALI-2

220-240 V

system 10.0 W

system 101 lm/W²

PC2

1 DALI Addr.

Physical

length 60 mm

width 60 mm


height 60 mm

adapter 402 mm

suspension 2000 mm


¹ Value of containing product at full load (undimmed)
² incl. consideration of optical losses, internal control unit losses
& operating device efficiency

Light distribution



| wide flood 67° | | | |
|----------------|----------|-------|--|
| h (m) | E0° (lx) | ø (m) | |
| 1 | 960 | 1.31 | |
| 2 | 240 | 2.63 | |
| 3 | 107 | 3.94 | |
| 4 | 60 | 5.26 | |
| 5 | 38 | 6.57 | |

Product drawing



Installation instructions

Lighting calculator

