

# NOBA 60 suspended 1 lamp

MOVE IT PRO

086-71001398W



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



## General

Ceiling , Track Suspended \_\_\_\_\_

rose gold \_\_\_\_\_

Converter Jet Black \_\_\_\_\_

IP20 \_\_\_\_\_

1040 lm \_\_\_\_\_

## LED

4000 K \_\_\_\_\_

CRI  $\geq 90$  \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

initial MacAdam  $\leq 2$  SDCM \_\_\_\_\_

R<sub>g</sub>: 97 , R<sub>f</sub>: 90 , R<sub>t(1-15)</sub>: 89 \_\_\_\_\_

MR 0.81 \_\_\_\_\_

MDER 0.74 \_\_\_\_\_

## Optical

wide flood \_\_\_\_\_

beam angle 67° \_\_\_\_\_

PstLM  $\leq 1.0$  <sup>1</sup> \_\_\_\_\_

SVM  $\leq 0.4$  <sup>1</sup> \_\_\_\_\_

## Electrical

DALI-2 \_\_\_\_\_

10.0 W \_\_\_\_\_

PC2 220-240V \_\_\_\_\_

104 lm/W \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_

## Physical

length 60 mm \_\_\_\_\_

width 60 mm \_\_\_\_\_


height 60 mm \_\_\_\_\_

402 (adapter) mm \_\_\_\_\_

suspension 2000 mm \_\_\_\_\_

<sup>1</sup> Value of containing product at full load (undimmed)


## Light distribution



wide flood 67°

h (m)	E0° (lx)	ø (m)
1	989	1.31
2	247	2.63
3	110	3.94
4	62	5.26
5	40	6.57

## Product drawing



## Lighting calculator



# NOBA 60 suspended 1 lamp

MOVE IT PRO  
086-71001398W



Project / Type

Notes

Count / Date

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.92	0.88	0.85	0.81
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF <sup>a</sup>	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF <sup>a</sup>	Luminaire Maintenance Factor		LSF	Lamp Survival Faktor	

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	27
B13	34
B16	43
C10	33
C13	42
C16	53

## Mounting accessories

### HOOK

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
traffic white	16	030-1000017
jet black	16	030-1000018

