

NOBA 60 suspended 1 lamp

MOVE IT PRO

086-71002357W



Project / Type

Notes

Count / Date



General

Ceiling , Track Suspended

gun metal

Converter Traffic White

IP20

1000 lm

LED

3500 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 97 , R_f: 90 , R_{t(1-15)}: 89

MR 0.7

MDER 0.63

Optical

wide flood

beam angle 67°

PstLM ≤ 1.0 ¹

SVM ≤ 0.4 ¹

Electrical

DALI-2

220-240 V

system 10.0 W

system 100 lm/W²

PC2

1 DALI Addr.

Physical

length 60 mm


width 60 mm

height 60 mm

adapter 402 mm

suspension 2000 mm


Light distribution



wide flood 67°

h (m)	E0° (lx)	ø (m)
1	951	1.31
2	238	2.63
3	106	3.94
4	59	5.26
5	38	6.57

Product drawing



¹ Value of containing product at full load (undimmed)

² FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions



Lighting calculator

