

ARY cable suspended 2 lamps

MOVE IT PRO

086-731023X8M



Project / Type

Notes

Count / Date



General

Ceiling , Track Suspended

special colours

Converter Jet Black

IP20

2130 lm

LED

3500 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 97 , R_r: 89 , R_{t(1-15)}: 87

MR 0.71

MDER 0.64

Optical

medium

beam angle 25°

PstLM $\leq 1.0^{1,2}$

SVM $\leq 0.4^{1,2}$

Electrical

DALI-2

220-240 V

system 28.2 W

system 76 lm/W³

PC2

1 DALI Addr.

Physical

cable 2000 mm


diameter 47 mm

height 110 mm

adapter 402 mm

Decorative pendant light inset made of aluminium; 2 lamps; cylindrical spotlight heads; surface special colours powder coated; light inset, incl. high power adapter + converter can be installed flexibly and without tools; power supplied via MOVE IT PRO system track profile; pendant fitting with 2000mm suspension, incl. feed (special colours), can be individually shortened; shades available as accessory in RAL colours velvet beige, madeira brown, kingfisher grey, woodpecker olive, signal white or signal black; accessories are listed separately; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3500 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 25° beam; degree of protection IP20; PC2; 220-240 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;


Light distribution



medium 25° combined

h (m)	E0° (lx)	ø (m)
1	9210	0.44
2	2300	0.89
3	1020	1.33
4	580	1.78
5	370	2.22

Product drawing



¹ combined ² Value of containing product at full load (undimmed)

³ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions



[086-731023X8M] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

08.04.2025